Triax HDMI cable

- Professional grade HDMI cable for a perfect high definition connection.
- · Sealed moulded diecast connectors.
- Gold plated contacts for quality transmission and tarnish resistance.
- EMI interference suppressed.
- Compatible with all HD resolutions.
- Ideal for connecting SkyHD boxes, DVD players and all other HDMI equipped AV equipment.



Technical data HDMI cable

TYPE		HDMI cable 2 m	
Art. No.		153411	
Length	m	2	
Ferrite		2	
Signal pairs		-	
- conductor		Tinned copper	
- conductor size	AWG	28	
- insulation material	7.1.7.5.	Foamed PE	
- Insulation core colour		White/Green	
		White/Brown	
		White/Blue	
		White/Red	
		White/Green	
Drain wire		Tinned copper	
Drain wire size	AWG	28	
Shield		AL/Mylar/Mylar	
Signal wire		,,	
- conductor		Tinned copper	
- conductor size	AWG	28	
- insulation material	AVVG	HDPE	
- Insulation core colour		White	
modiation core colour		Green	
		Orange	
		Yellow	
		Red	
		Purple	
Outer shield		•	
- conductor	shield 1	Aluminium mylar	
- conductor size	shield 2	Tinned copper (braiding)	
Outer shield		· · · · ·	
- overall diameter	mm	Ø 7.3	
- material		PVC	
Electrical data			
Differential impedance	Ohm	100 (± 10%)	
Max differential delay	ns/m	5.05	
Max intra - pair skew	ps	151	
Far-end crosstalk (@ 1-5000 MHz)	dB	- 26	
Connector			
Pin		19	
Metal shell		Parl chrome plated	
Connector impedance	Ohm	100 (± 15%)	
		, , , ,	